

MATERIAL SAFETY DATA SHEET

MANUFACTURED FOR: PJH BRANDS
ADDRESS: 8747 E Via de Commercio, Scottsdale, AZ 85258 USA
EMERGENCY PHONE: CHEMTREC® 703-527-3887 SHIPPER: PJH BRANDS, Contract #CCN17400
DATE REVISED: 9/30/13
INFORMATION PHONE: 1-480-991-8002
REASON REVISED: Updated

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: PJ1 TRACKBITE
PRODUCT CODE: SP-163
PRODUCT CLASS: Bulk
CONTROL CODE: SP-163

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HEALTH= 2
FIRE= 3
REACTIVE = 0
PERSONAL
PROTECTION = H

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENTS	C.A.S. NUMBER	EXPOSURE LIMITS TLV/PEL
*ANTISAL 1A	108-88-3	100/150 PPM
*SKELLYSOLVE B	110-54-3	50/50 PPM
ALCOHOL ANHYDROUS	64-17-5	1000/1000 PPM
2-PROPANOL	67-63-0	400/400 PPM

(*) INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 TITLE III AND CFR 372

SECTION III - PHYSICAL DATA

SPECIFIC GRAVITY: 0.78
BOILING RANGE: 170-232 DEGREE'S F.
VAPOR DENSITY: HEAVIER THAN AIR.
VAPORATION RATE: SLOWER THAN ETHER.
APPEARANCE & ODOR: AMBER LIQUID, FRUITY ALCOHOL FRAGRANCE
WEIGHT PER GALLON: 6.50

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: FLAMMABLE LIQUID - CLASS 1B
FLASH POINT: 20 DEGREE'S F. PMCC
LEL: 1.00%

MATERIAL SAFETY DATA SHEET

EXTINGUISHING MEDIA:

Based on the NFPA guide, use dry chemical, alcohol foam, carbon dioxide, or other extinguishing agent suitable for class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drenching the burning material.

SPECIAL FIREFIGHTING PROCEDURES:

Keep unnecessary people away, insulate area. Stay upwind, wear self-contained breathing apparatus. Use emergency response guidelines (DOT P5800.4 GUIDE 26)

UNUSUAL FIRE & EXPLOSION HAZARDS:

Exposure to heat will produce irritating vapors. Insulate from heat, electrical equipment, sparks & open flame. Closed containers may explode when subject to high heat .
Dense smoke & toxic fumes will result during combustion creating a health hazard.

SECTION V- HEALTH HAZARDS AND PERSONAL PROTECTION INFORMATION

FIRST AID:

EYES:	Immediate flush for at least 15 minutes, while holding eyelids open. Call a physician at once.
SKIN:	Immediate flush with water for at least 15 minutes For a large splash flood body under a shower. Call a physician at once
INGESTION:	Do not induce vomiting. Give water. Call a physician at once
INHALATION:	Remove to fresh air. Treat symptoms. Call a physician at once

TOXICOLOGY INFORMATION:

ACUTE TOXICITY STUDIES: No toxicity studies have been conducted on this product
PRIMARY ROUTE(S) OF EXPOSURE
EYE CONTACT: Can cause irritation.
SKIN CONTACT: Can cause irritation.
INHALATION: Not a problem, except at high temperatures.

SYMPTOMS OF EXPOSURE:

ACUTE: Unusual use practices and/or poor ventilation can cause irritation of eyes and respiratory tract.

AGGRAVATION OF EXISTING CONDITIONS:

A review of available data does not identify any worsening of existing conditions not elsewhere in this MSDS

RESPIRATORY PROTECTION:

If it is possible to generate significant levels of vapor or mists, a NIOSH approved or equivalent respirator is recommended.

VENTILATION:

General ventilation is recommended. Additional local exhaust ventilation is recommended where vapors, mists or aerosols may be released.

PROTECTIVE EQUIPMENT:

Wear impervious gloves, apron, & splash goggles where exposure is possible.
Launder contaminated clothing before reuse.

MATERIAL SAFETY DATA SHEET

SECTION VI - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: HI TEMPERATURES, OPEN FLAME

INCOMPATIBILITY: STRONG OXIDIZERS

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING MAY PRODUCE IRRITATING, TOXIC METAL FUME. HYDROGEN CHLORIDE, CARBON MONOXIDES, NITROGEN'S AND SULFURS.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
REMOVE SOURCES OF IGNITION, COVER WITH INERT ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER. OBEY ALL FEDERAL, STATE AND LOCAL LAWS. THIS IS A RCA HAZARDOUS WASTE PER TITLE 40 CFR 261, CLASSIFIED AS D001

WASTE DISPOSAL METHODS:
OBEY REVELANT FEDERAL, STATE AND LOCAL LAWS. DO NOT CONTAMINATE ANY LAKES STREAMS, PONDS OR UNDERGROUND WATER SUPPLIES.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATION PROTECTION:
USE NIOSH APPROVED ORGANIC VAPOR RESPIRATORY EQUIPMENT WHEN TLV IS EXCEEDED.

VENTILATION:
LOCAL EXHAUST RECOMMENDED.
MECHANICAL EXHAUST RECOMMENDED.

PROTECTIVE GLOVES:
IMPERMEABLE GLOVES TO MINIMIZE SKIN CONTACT.

EYE PROTECTION:
CHEMICAL SPLASH GOGGLES OR FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT:
EYE WASH FOUNTAIN, SAFETY SHOWER.

HYGIENE PRACTICES:
WASH CONTAMINATED CLOTHES BEFORE REUSE.

MATERIAL SAFETY DATA SHEET

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

CAUTION OSHA CLASS FLAMMABLE LIQUID, VAPORS ARE HEAVIER THAN AIR AND TEND TO ACCUMULATE IN LOW LAYING AREAS SUCH AS SINKS, SUMPS AND ALONG FLOORS. USE WITH ADEQUATE EXPLOSION PROOF VENTILATION. ISOLATE FROM SOURCES OF HEAT, SPARKS OR FLAMES. EXTINGUISH ALL SOURCES OF IGNITION, INCLUDE REMOTE PILOTS AND LIGHTS. MAYBE HARMFUL IF SWALLOWED OR INHALED

OTHER PRECAUTIONS:

AVOID PERSONAL CONTACT, KEEP OUT OF REACH OF CHILDREN, WASH HANDS BEFORE EATING OR SMOKING. DO NOT PUNCTURE, DROP OR SLIDE CONTAINER. KEEP CONTAINER CLOSED.

SECTION X REGULATORY INFORMATION

FEDERAL REGULATIONS:

See Section II for hazardous ingredients as defined by OSHA Hazardous communication rule, 29 CFR 1910, 1920

SARA TITLE II SECTION 313

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to know act of 1986 and of 40 CFR 372:

CHEMICAL NAME	CAS #	PERCENT BY WEIGHT
*TOLUENE	108-88-3	<5.00%
*HEXANE	110-54-3	<25.00%

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All compounds in this product are listed, or are excluded from listing, on the U.S. Toxic Substances control act (TSCA) 8(B) inventory

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40CFR401.15:

None of the ingredients in this product are specifically listed.

CLEAN ACT, 40CFR 60, SECTION 111, 40 CFR 61, SECTION 112:

None of the ingredients in this product are specifically listed.

CONEG-COALITION OF NORTHWEST GOVERNORS:

This product contains none of the constituent heavy metals regulated by CONEG (i.e. total cadmium, chromium, lead & mercury).

TRANSPORTATION 49, CFR 172-101

CLASS 3 (FLAMMABLE LIQUIDS), II

D.O.T. PROPER SHIPPING NAME:

ADHESIVE, 3, UN1133, PGII

CLEAN AIR AMENDMENTS OF 1990

This product contains no ozone depleting substances (ODS)

